

# 2" - 3" Plastic Commercial Filters

## Product Features

- Available filtration – 50, 75, 120, 155, & 200 mesh
- Filtering element – polypropylene disk or stainless steel screen
- Pre-molded pressure taps
- Stainless steel clamp closure

### “Y” Filter Features

- Max Working pressure 116 PSI @ 68° F
- Constructed from chemical resistant polypropylene reinforced with fiber glass

### “T” Filter Features

- Max Working pressure 145 PSI @ 68° F
- Constructed from chemical resistant polyamide reinforced with fiber glass
- “T” filter’s designed for inline or angle installation for easy cleaning
- Large Cartridge 2” & 3” THF with stainless steel clamp
- Extra Large Cartridge 2” & 3” TIF with stainless steel clamp



Filter Model	Filter Size	Filtration Area (Sq. In.)		Normal Flows (GPM)	Pressure Loss (PSI)
		Disk	Screen		
YHF	2"	217	197	110	1.5
YHF	3"	217	197	220	2
THF	2"	217	197	132	3
THF	3"	217	197	220	3
TIF	2" XL	290	260	174	3
TIF	3" XL	290	260	220	3

\*Based on 120 mesh filtration

## Irritec USA Inc.

1420 N. Irritec Way - Fresno, CA 93703

Tel: (559) 275-8825 - Fax: (559) 275-9555 - Toll Free: (877) 298-2075

[www.irritec.com](http://www.irritec.com)

*don't wait for rain™*