

PP WOVEN GROUND COVER (SULZER)

SR NO.	TYPICAL PROPERTIES	TEST METHOD	M.A.R.V.
1	MASS PER UNIT AREA	ASTM D 5261	3.2 Oz/YD ² (108gsm)
2	TENSILE STRENGTH (MD x CD)	ASTM D 4632	190 lbs x 110 lbs
3	ELONGATION (MD x CD)	ASTM D 4632	MIN 15%
4	BURST STRENGTH (MULLEN)	ASTM D 3786	330 PSI
5	TRAPEZOIDAL TEAR	ASTM D 4533	65 lbs x 60 lbs
6	PUNCTURE STRENGTH	ASTM D 4833	70 lbs
7	A.O.S.	ASTM D 4751	40 US SIEVE
8	FLOW RATE (FALLING HEAD)	ASTM D 4491	17 GPM/FT ²
9	PERMITIVITY	ASTM D 4491	0.22 SEC ⁻¹
10	UV STABILITY	ASTM D 4355	70% @ 2500 HRS
11	COLOR	WHITE WITH GREEN/BLUE/BLACK STRIPE	

Above technical data are mean values based on production and independent institute tests for guidance only.

There can be a tolerance of 15% in the above test result

Use of some kind of Pesticides and chemicals can lower the UV resistance

Ground covers have to be placed on clean surfaces which are free from rocks and weeds

