

AC 8000 “S” series (4 to 12 stations)

The Galcon 8000S AC is an indoor irrigation and propagation controller designed to operate 4, 6, 9 & 12 irrigation control valve + master valve/pump start. In addition to outstanding durability, the 8000S AC features a large easy-to-program LCD screen and four buttons for programming. This controller offers the ultimate flexibility in scheduling by offering independent programming of each valve and the ability to operate two valves simultaneously.

Programming can be set by day of the week (daily/weekly) with irrigation duration as short as 1 minute to as long as 12 hours and up to 4 start times per valve may be used. Or, in cyclical mode, irrigation duration as short as 1 second to as long as 12 hours with a cycle as short as every 1 minute to as long as every 30 days. In addition, the programmable watering window will limit watering to desired hours of operation.

The available sensor input can be used with a rain sensor, soil moisture sensor, etc. to conserve water. The sensor input is assigned to individual valves providing you with the flexibility of preventing irrigation in areas that are exposed to rain (lawn) and allowing irrigation to areas that are not exposed to rain (covered patio). Monthly water budgeting can be used to adjust irrigation from 10% - 190%.

Rain Delay of up to 30 days and auto re-start.

Automatic, semi-automatic and manual mode for each valve or all of the valves simultaneously while automatic short circuit detection isolates the shorted valve, provides a visible “alarm” on the LCD and continues irrigation for the rest of the valves.

Item	Package Dimensions in cm	Master Box Dimensions	Master Case Quantity	Pallet Quantity	Master Cases per Pallet	Measurement of Pallets in cm	Total units per 20' container	Total units per 40' container	Per unit KG	Master box KG
AC9/AC12	23x30x12.5	40x31x25	3	189	63	120x100x162	1,890	3,780	2.05	6.7

S/N	Product
GAEBS0002U1	8004S AC-4S indoor »
GAEBS0002S4	8004S AC-4S in outdoor casing »
GAE5S0002U1	8056S AC-6S indoor »
GAE5S000S4	8056S AC-6S in outdoor casing »
GAE5S0002S4	8059S AC-9S in outdoor casing »
GAE4S0002S4	80512S AC-12S in outdoor casing »

Model	AC-4S 8004S - 4 stations AC-6S 8056S - 6 stations AC-9S 8059S - 9 stations AC-12S 80512S - 12 stations
Input	220VAC 50Hz (110VAC 60Hz available on request)
Output	24VAC 0.83A
Standard	CE
Back up battery	9V
Operated Valve	24VAC



AC-4S/6S indoor



AC-4S/6S/9S outdoor