a World of Plas	Product spe	cification sheet
Document number:		Version: 2
Author:	BDR	
Last updated on:	07/10/2014	Page 1 of 2

1 General information

Product: Hyticlear

Description: Transparent coextruded 3-layer film stabilised with HALS

Application: Greenhouse cover

Typical properties: High light transmission

2 <u>Technical data</u>

Property			Турі	cal value	
Thickness			0.180	mm	
Dart drop	(ASTM D1709)		650	g	
Tensile at break	(ASTM D882)	MD TD	23 23	MPa MPa	
Elongation at break	(ASTM D882)	MD TD	550 650	% %	
Total light transmission	n		88	%	
Direct light transmission			65	%	
Diffuse light transmiss	sion		23	%	
Thermicity			40	%	
Min/max ambient temperature			-50 / 85	°C	

MD = machine direction TD = transversal direction



Distribué par / Distributed by : Groupe Horticole Ledoux inc.

785, rue Paul Lussier, Ste-Hélène de Bagot Québec, Canada, JOH 1M0

Tel.: 1 (888) 791.2223

All information supplied by or on behalf of HYPLAST in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by research and believed reliable, but HYPLAST assumes no liability whatsoever in respect of application, processing or use made of the aforementioned information or products, or any consequence thereof. The buyer undertakes all liability in respect of the application, processing or use of the aforementioned information or product, whose quality and other properties he shall verify, or any consequence thereof. No liability whatsoever shall attach to HYPLAST for any infringement of the rights owned or controlled by a third party in intellectual, industrial or other property by reason of the application, processing or use of the aforementioned information or products by the buyer.

a World of Plas	Product spe	cification sheet
Document number:		Version: 2
Author:	BDR	
Last updated on:	07/10/2014	Page 2 of 2

3 Functional information

Product: Hyticlear

Lifetime: Film stabilised for 300-350 Kly (unit of irradiation energy)

e.g. 4 years guaranteed in Benelux (80 Kly/Year)

Attention: Special attention should be paid to the positioning of fork-lift as the film directly on

top of the pallet is vulnerable to local pressure build-ups and may tear if not handled with care. Special attention should also be paid when opening the packaging, as

incidental cutting of straps may cause rolls to fall off the pallet.

Storage: The product must be stored indoors and must be used within 3 years after delivery.

Use: Hyplast will not be liable to claims or restitutions when the product is used in

combination with too high a concentration of chlorine or sulphur. Pesticides may contain substances that may affect the specification of our products. Please contact

our customer service for questions.

Disposal: The product should be disposed of in an environmental friendly way.

Complaints: In case of a complaint, please contact our customer service.



Distribué par / Distributed by : Groupe Horticole Ledoux inc.

785, rue Paul Lussier, Ste-Hélène de Bagot Québec, Canada, JOH 1M0

Tel.: 1 (888) 791.2223

All information supplied by or on behalf of HYPLAST in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by research and believed reliable, but HYPLAST assumes no liability whatsoever in respect of application, processing or use made of the aforementioned information or products, or any consequence thereof. The buyer undertakes all liability in respect of the application, processing or use of the aforementioned information or product, whose quality and other properties he shall verify, or any consequence thereof. No liability whatsoever shall attach to HYPLAST for any infringement of the rights owned or controlled by a third party in intellectual, industrial or other property by reason of the application, processing or use of the aforementioned information or products by the buyer.