

RKW Hyplast NV

Document number:		Version: 1
Author:		
Last updated on:	10/02/2004	Page 1 of 2

## 1 General information

Product: Hytilux

Description: Transparent coextruded 3-layer film stabilised with HALS with a high percentage of V.A. and anti-fog package

Application: Greenhouse cover

Typical properties: High light transmission  
Thermic  
Anti-fog

## 2 Technical data

Property	Typical value		
Thickness	0.180	mm	
Dart drop (ASTM D1709)	900	g	
Tensile at break (ASTM D882)	MD	23	MPa
	TD	24	MPa
Elongation at break (ASTM D882)	MD	525	%
	TD	650	%
Total light transmission	88	%	
Direct light transmission	58	%	
Diffuse light transmission	30	%	
Thermicity	20	%	
Min/max ambient temperature	-50 / 85	°C	

MD = machine direction  
TD = transversal direction



Distribué par / Distributed by :  
Groupe Horticole Ledoux inc.  
785, rue Paul Lussier, Ste -Hélène de Bagot  
Québec, Canada, J0H 1M0  
Tel. : 1 (888) 791.2223

All information supplied by or on behalf of RKW HYPLAST NV in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by research and believed reliable, but RKW HYPLAST NV assumes no liability whatsoever in respect of application, processing or use made of the aforementioned information or products, or any consequence thereof. The buyer undertakes all liability in respect of the application, processing or use of the aforementioned information or product, whose quality and other properties he shall verify, or any consequence thereof. No liability whatsoever shall attach to RKW HYPLAST NV for any infringement of the rights owned or controlled by a third party in intellectual, industrial or other property by reason of the application, processing or use of the aforementioned information or products by the buyer.

RKW Hyplast NV

Document number:		Version: 1
Author:		
Last updated on:	10/02/2004	Page 2 of 2

### 3 Functional information

Product:	Hytilyx
Lifetime:	Film stabilised for 350 Kly
Attention:	Special attention should be paid to the positioning of fork-lift as the film directly on top of the pallet is vulnerable to local pressure build-ups and may tear if not handled with care. Special attention should also be paid when opening the packaging, as incidental cutting of straps may cause rolls to fall off the pallet.
Storage:	The product must be stored indoors and must be used within 3 years after delivery.
Use:	RKW Hyplast NV will not be liable to claims or restitutions when the product is used in combination with too high a concentration of chlorine or sulphur. Pesticides may contain substances that may affect the specification of our products. Please contact our customer service for questions.
Disposal:	The product should be disposed of in an environmental friendly way.
Complaints:	In case of a complaint, please contact our customer service.



Distribué par / Distributed by :  
Groupe Horticole Ledoux inc.  
785, rue Paul Lussier, Ste -Hélène de Bagot  
Québec, Canada, J0H 1M0  
Tel. : 1 (888) 791.2223

All information supplied by or on behalf of RKW HYPLAST NV in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by research and believed reliable, but RKW HYPLAST NV assumes no liability whatsoever in respect of application, processing or use made of the aforementioned information or products, or any consequence thereof. The buyer undertakes all liability in respect of the application, processing or use of the aforementioned information or product, whose quality and other properties he shall verify, or any consequence thereof. No liability whatsoever shall attach to RKW HYPLAST NV for any infringement of the rights owned or controlled by a third party in intellectual, industrial or other property by reason of the application, processing or use of the aforementioned information or products by the buyer.